

Appln. No. 09/939,267

Attorney Docket No. 10541-466

## I. Amendments to the Claims

1-27. (Canceled)

28. (New) A system for a backlit display, comprising:

a plurality of light emitting diodes connected together in series;

a plurality of parallel elements connected in parallel with the plurality of light emitting diodes, and wherein the plurality of light emitting diodes are adapted to provide back lighting for a liquid crystal display;

a current monitor connected with the plurality of light emitting diodes that measures an amount of current flowing from the plurality of light emitting diodes and generates a current flow signal;

a temperature sensor in communication with the plurality of light emitting diodes to measure a temperature of the light emitting diodes and generate a temperature signal corresponding to the temperature;

a voltage converter that supplies a current to the plurality of light emitting diodes as a function of the current flow signal, a commanded current signal, and the temperature signal, when in a first mode below a threshold temperature the voltage converter being in electrical communication with the plurality of parallel elements to automatically increase a voltage across a parallel element of the plurality of parallel elements based on the current flow signal, thereby causing the current to flow through the parallel element and around a light emitting diode of the plurality of light emitting diodes upon an open circuit failure of the light emitting diode and maintain a consistent brightness, and when in a second mode above a threshold temperature the voltage converter being configured to reduce the current to the plurality of light emitting diodes as a function of the temperature signal.



BRINKS HOFER GILSON & LIONE  
PO Box 10395  
Chicago, IL 60610

Appln. No. 09/939,267

Attorney Docket No. 10541-466

29. (New) The device of claim 28, further comprising a temperature derating circuit that reduces the current to the plurality of light emitting diodes the temperature signal exceeds the temperature threshold.

30. (New) The device of claim 29, wherein a first feedback loop is formed by providing the temperature signal to the temperature derating circuit.

31. (New) The device of claim 29, further comprising a luminance display processor configured to adjust the commanded current signal based on the temperature signal to provide the consistent brightness from the plurality of light emitting diodes.

32. (New) The device of claim 31, wherein the luminance display processor adjusts the commanded current signal to as a function of a measured temperature and a temperature correction factor table.

33. (New) The device of claim 31, wherein a first feedback loop is formed by providing the temperature signal to the temperature derating circuit.

34. (New) The device of claim 33, wherein the second feedback loop is formed by adjusting the commanded current signal in the luminance display processor based on the temperature signal.

35. (New) The device of claim 34, wherein the commanded current signal is provided to the temperature derating circuit from luminance display processor.

36. (New) The system of claim 28, wherein the commanded current signal comprises a direct current signal.



BRINKS HOFER GILSON & LIONE  
PO Box 10395  
Chicago, IL 60610

Appln. No. 09/939,267

Attorney Docket No. 10541-466

37. (New) The device of claim 28, wherein the commanded current signal comprises a pulse width modulated signal.

38. (New) The device of claim 28, wherein the plurality of parallel elements comprises a plurality of zener diodes.

39. (New) The device of claim 28, wherein a parallel element is connected in parallel with a light emitting diode of the plurality of light emitting diodes.

40. (New) The device of claim 28, wherein a parallel element is connected in parallel with multiple light emitting diodes of the plurality of light emitting diodes.

41. (New) The device of claim 28, wherein the temperature sensor measures a solder temperature near a light emitting diode.

42. (New) The device of claim 28, wherein the temperature sensor comprises a temperature dependant resistor.

43. (New) The device of claim 42, wherein a terminal of the temperature dependant resistor and a cathode terminal of a light emitting diode of the plurality of light emitting diodes are thermally interconnected.



BRINKS  
HOFER  
GILSON  
& LIONE  
BRINKS HOFER GILSON & LIONE  
PO Box 10395  
Chicago, IL 60610

Appl. No. 09/939,267

Attorney Docket No. 10541-466

## II. Remarks

Reconsideration and re-examination of this application in view of the above amendments and the following remarks is herein respectfully requested.

Claims 1-27 have been cancelled. Claims 28-43 remain pending.

*New claims*

None of the references cited by the examiner teach a system for a backlit display that have a first mode that bypasses failed LEDs and compensates to maintain a consistent brightness below a temperature threshold, and a second mode that derates the current about the temperature threshold. Accordingly, none of the references of record teach or suggest the present invention provided in independent claim 28. Further claims 29-43 depend from claim 28 and are, therefore, patentable for at least the same reasons given above in support of claim 28.

*Conclusion*

In view of the above amendments and remarks, it is respectfully submitted that the present form of the claims are patentably distinguishable over the art of



BRINKS HOFER GILSON & LIONE  
PO Box 10395  
Chicago, IL 60610

Appln. No. 09/939,267


Attorney Docket No. 10541-466

record and that this application is now in condition for allowance. Such action is respectfully requested.

Dated: August 14, 2006

BRINKS HOFER GILSON & LIONE  
P.O. Box 10395  
Chicago, IL 60610  
(734) 302-6000

Respectfully submitted by,



Eric J. Sosenko  
Reg. No.: 34,440  
Attorney for Applicant(s)

BRINKS
HOFFER
GILSON
LIONE

BRINKS HOFER GILSON & LIONE  
PO Box 10395  
Chicago, IL 60610